

SMART JOINTER

SmartJointer is a filling and smoothing putty paste for manual application indoors and outdoors.
The product is suitable for filling tile and tile grout joints in kitchens and bathrooms.

PERFORMANCE

Consumption as smoothing: 0.9 kg/m²/mm approx.
Applied on tile joints: 0.24 kg/m²/mm approx.

PROPERTIES

- High adhesion on a wide variety of substrates; tiles, ceramics, plaster, plasterboard, concrete, bricks, stone, mortar, painted surfaces, etc.
- Good resistance to water and ambient humidity.
- Retains flexibility after drying.
- Easy to apply and sand

TECHNICAL INFORMATION

PROPERTIES	SPECIFICATION	UNIT	METHOD
Features	Acrylic Putty		
Colour	White cream		
Non-volatile content	83-85	%	UNE-EN ISO 3251:2020
Density	1,6±0,1	g/cm ³	UNE-EN ISO 2811-1
Thickness of application	Up to 4mm per pass		
Drying time to touch	5-6	Hours	
Complete drying time	8-10	Hours	

APPLICATION

- Before applying **SmartJointer**, it is essential to check that the substrate is stable and completely clean. Stir the contents before use. Application material: spatula or trowel. Maximum application thickness up to 4 mm per coat.
- Do not apply at temperatures below 10°C and above 35°C and humidity above 80%.
- Do not apply on heated surfaces or in direct sunlight.
- Do not apply on substrates subject to permanent humidity. This product is not suitable for coating surfaces that are to be painted afterwards.
- Depending on the environmental conditions and the ventilation of the workspace, it will be necessary to allow 12-24 hours to elapse before applying Smartcret® microcement.

SPECIAL PRECAUTIONS

It is essential to follow the instructions on the label of the container. For further information, please refer to the product safety data sheet. Empty containers must be disposed of in accordance with current legislation. To prevent the product from drying out or thickening, close the lid after each use.

PRESENTATION

It comes in 1.5L containers.

TOOL CLEANING

The tools are washed with water immediately after use

STORAGE CONDITIONS

The product should be stored in its original closed container and protected from the weather at temperatures between 10°C and 30°C, in a dry and well ventilated place, away from heat sources and direct sunlight. The shelf life is 1 year from the date of manufacture, if stored properly.